

snom

snom

## Contact

Snom Technology GmbH  
Aroser Allee 66  
13407 Berlin, Germany

Tel.: +49 (0)30 39833-0  
Fax: +49 (0)30 39833-111  
sales@snom.com  
www.snom.com



More details  
and information on  
[snom.com](https://www.snom.com)



# Connecting your Business

Product overview



	<b>D812</b>	<b>D815W</b>	<b>D862</b>	<b>D865</b>	<b>Expansion Module D8C</b>
<b>Display</b>	5 inch IPS display (480 x 272)	5 inch IPS display (480 x 272)	5 inch swivel IPS display (1280 x 720)	5 inch swivel IPS display (1280 x 720)	6,8 inch IPS display (21:9)
<b>Wired Interfaces</b>	EHS, 1x USB	EHS, 2x USB	EHS, 1x USB	EHS, 2x USB	2x USB
<b>Ethernet/Switch</b>	2x Gigabit	2x Gigabit	2x Gigabit	2x Gigabit	-
<b>Programmable Buttons (LED)</b>	8	10	8	10	20
<b>Extension module D8C</b>	●	●	●	●	●
<b>Integrated Wireless Interfaces</b>	-	WiFi	-	WiFi, Bluetooth	-

All D8xx devices have antibacterial housing.  
All desk phones have a 3 year warranty.



**D785/D385N**



**D735/D335**



**D717**



**D713**



**Expansion Module  
D7C**

	<b>D785/D385N</b>	<b>D735/D335</b>	<b>D717</b>	<b>D713</b>	<b>Expansion Module D7C</b>
<b>Display</b>	4.3 inch TFT colour display	2.7 inch TFT colour display	2.7 inch TFT colour display	2.8 inch TFT colour display	6.8 inch TFT colour display
<b>Wired Interfaces</b>	EHS, USB	EHS, USB	EHS, USB	EHS	USB
<b>Ethernet/Switch</b>	2x Gigabit	2x Gigabit	2x Gigabit	2x Gigabit	-
<b>Programmable Buttons (LED)</b>	D785: 24 multicolour (6 physical) D385N: 48 multicolour (12 physical)	32 multicolour (8 physical)	3 multicolour	4	16
<b>Extension module D7C</b>	●	●	●	○	●
<b>Bluetooth Compatibility</b>	D785 ● D385N ○	○	○	○	○
<b>Built-in WiFi</b>	○	○	○	○	○

○ Expandable via USB dongle.  
All desk phones have a 3 year warranty.



**D140**



**D150**

<b>Display</b>	2.8 inch greyscale display	2.8 inch greyscale display
<b>Wired Interfaces</b>	EHS, USB	EHS, USB
<b>Ethernet/Switch</b>	2x 10/100 Mbit	2x Gigabit
<b>Programmable Buttons (LED)</b>	2	2
<b>Colour</b>	Slate grey	Slate grey



**PA1+**

- 6.5 watt Class D amplifier
- 4 controllable outputs
- Announcements via SIP and multicast
- Robust housing
- Wall and ceiling mounting possible



**SP800**

- 2x USB 2.0 type A sockets
- HD audio
- TLS & SRTP
- 2 LED indicators
- 8 SIP identities
- LDAP
- Control via soft client
- 110 mm x 110 mm x 30.2 mm



**M10 SC**



**M65**



**M85**



**M30**



**M70**



**M80**



**M90**

	M10 SC	M65	M85	M30	M70	M80	M90
<b>Display</b>	1.8 inch single-colour	2 inch 176 x 220 px TFT	2 inch 176 x 220 px TFT	2 inch 176 x 220 px TFT	2 inch 240 x 320 px TFT	2 inch 240 x 320 px TFT	2 inch 240 x 320 px TFT
<b>Shockproof</b>	○	○	●	○	●	●	●
<b>IP65 Protection Class</b>	○	○	●	○	○	●	●
<b>Standby time</b>	168 hours	250 hours	200 hours	350 hours	200 hours	200 hours	200 hours
<b>Talk time</b>	9 hours	18 hours	17 hours	22 hours	17 hours	17 hours	17 hours
<b>Dimensions</b>	173 x 49 x 27 mm	141 x 48 x 24 mm	152 x 48 x 28 mm	128 x 53 x 25 mm	118 x 46 x 22 mm	122 x 48 x 22 mm	122 x 48 x 22 mm
<b>Alarm button</b>	○	○	●	○	●	●	●
<b>Additional functions</b>	-	Vibration, belt clip, illuminated keypad	Vibration, illuminated keypad, IP65, Bluetooth, three additional alarm functions	Belt clip	Robust design, Bluetooth, illuminated keypad	Robust design, Bluetooth, illuminated keypad	Anti-bacterial coating, Bluetooth, illumi- nated keypad
<b>Compatible with the base stations</b>	<b>M100 SC</b>	<b>M400, M900</b>	<b>M400, M900</b>	<b>M400, M900</b>	<b>M400, M900</b>	<b>M400, M900</b>	<b>M400, M900</b>



**M100 SC**



**M900 / Outdoor**



**M400**

<b>Cell type</b>	Single	Multicell up to 1,000 base stations	Single
<b>Number of handsets supported</b>	10	Up to 4,000	10
<b>Number of simultaneous calls</b>	6	Up to 8 per base	10
<b>Wideband Codec</b>	Codec G.722	Codec G.722	Codec G.722
<b>PoE support</b>	yes	yes	yes
<b>Compatible with devices</b>	<b>M10 SC</b>	<b>M30, M65, M85, M70, M80, M90</b>	<b>M30, M65, M85, M70, M80, M90</b>



**M500**  
DECT base station

- Can be used in single and dual cell mode
- Up to 48 SIP accounts
- Up to 8 simultaneous calls
- 10 handsets per base in single cell mode / 8 handsets per base in dual cell mode
- LDAP + XML Phonebook
- Shared Call Emulation



**M58 DECT**

- Display: 5 inch
- Wireless Interfaces: DECT, Bluetooth
- Programmable function keys: 8
- Shared Call Emulation
- Compatible with the base station **M500**



**M55**

- Display: 2.4 inch
- Standby: 240 hours
- Talk time: 19 hours
- Dimensions: 188 x 55 x 35 mm
- Programmable function keys: 6
- Shared Call Emulation
- Compatible with the base station **M500**



New

**M56**

- Protection class IP67
- Alarm functions
- Ideal for harsh working environments
- Antibacterial surface
- Programmable function keys: 6
- Bluetooth
- Compatible with the base station **M500**



### A330D/A330M

Weight: 220 g / 140 g

USB: yes

Audio bandwidth: Wideband ETSI

Frequency: 20 to 20,000 Hz

Remote control: yes

Passive noise cancellation: yes



### Coming soon A350M

Weight: 155 g

Bluetooth: yes

Audio bandwidth: Wideband ETSI

Frequency: 20 to 20,000 Hz

Remote control: yes

Passive noise cancellation: yes



### A310D / A310M

Weight: 209 g / 129 g

Audio bandwidth: Wideband ETSI

Frequency: 20 to 20,000 Hz

Remote control: no

Passive noise cancellation: yes



### A170 DECT Headset

Weight: 22 g

DECT: yes

Audio: Wideband ETSI

Talk time: up to 6 hours

Passive noise cancellation: yes



### A150 Micro DECT Headset

Weight: 23 g

DECT: yes

Audio: Wideband ETSI

Talk time: up to 6 hours

Passive noise cancellation: yes

### For multicell operation:



### A190 DECT headset

Weight: 45 g

DECT: yes

Audio: Wideband ETSI

Talk time: up to 7 hours

Wideband voice transmission

Compatible with base stations **M400, M900**



### C620

- Maximum flexibility thanks to wireless design
- Maximum range thanks to DECT technology
- Two cordless DECT microphones
- HD audio quality with G.722 codec support
- Up to 24 hours talk time
- Charging cradle included

### C52-SP

- Connection via DECT to **C620** and with **A230** to Snom desk phones.
- Battery or mains operation
- Up to 12 hours talk time and up to 70 hours Standby



### C300

- Bluetooth and USB
- 6 beamshape microphones
- Multicolour LED status indicator
- Large 5,000 mAh battery
- USB output for smartphone connection
- NFC

### M9B

- Wireless functions:
- Bluetooth Class 2, DECT range up to 50 m, LED display
- Compatibility:
- M900, M70, M80, M85, M90**
- Installation:
- Up to 10 gateways per M900, up to 1,000 gateways per installation

### M9T

- Built-in motion sensor
- Long battery life thanks to Bluetooth LE

